

Boiler Safety Valves DN40



PUCO

Boiler Safety Valves DN40 - 1½ x 2" KB

DUCO boilerválves to protect closed potable heated water systems against excessive pressure.

Application

The boiler valve has to be used in a closed drinking water system. Only use the valve in a dry and frostfree location.

Min/Max. system temp. 0°C / + 95°C

Safety

Check whether the max. capacity and the opening pressure that are indicated on the valve match the values of the system.

All Duco safety valves meet the requirements of the Pressure Equipment Directive (PED) "Directive 2014/68/EU Module B/Module D". The quality system also complies with the NEN-EN-ISO 9001

NORM: NEN-EN 1491

Lever - Brass CW617N

Adjustment screw - Brass CW617N

Indication label - Aluminium

Valve spindle - Brass CW617N

Preset spring - Spring steel DIN 17223 Zinc plated

Spring cover - Steel Zinc plated



Lift limiter - Steel Zinc plated

Membrane - EPDM 70'Shore Peroxide cured

Valve disk - Brass CW617N

Valve body - Brass CW617N - Pb<2,2%

Valve seal - EPDM 70'Shore Peroxide cured



Safety Valves DN40

Article number	Set pressure bar	Heating capacity kW
1151-0-06-11	6	600
1151-0-07-11	7	600
1151-0-08-11	8	600
1151-0-09-11	9	600
1151-0-10-11	10	600

PUCO

PenTec bv
Edisonweg 7
3442 AC Woerden
The Netherlands

Tel. +31 (0)182 503 100
E-mail info@pentecbv.nl
Internet www.duco.nl
www.pentecbv.nl